Beacon Modular Ranch & Cape Homes - INCLUDED FEATURES

Interior

Smooth Finish Flat Ceiling Throughout Coveless Ceiling 8'0" Sidewall Height 30'0" Floor Width **Primed Smooth Drywall Throughout**

Primed Smooth Drywall Throughout

Lucerne/Innovation Carpet with Rebond Carpet Pad Metal Interior Passage Sets Pre-Hung Door Jambs Mortise Hinges Smoke Detectors with Battery Back-Up White 6-Panel Interior Doors Residential Switches & Receptacles Perimeter Floor Registers & Boots

<u>Kitchen</u>

Choice of Autumn or Messina Oak Cabinetry 42" Lined Overhead Cabinets with Adjustable Shelves Hardwood Mission Flat Panel Cabinet Doors

Base Shelf in Kitchen Base Cabinets Deluxe Roller Drawer Guides Brushed Nickel Cabinet Hardware Hidden Hinges on Cabinets Cabinet Crown Moulding

Laminate Countertops with Laminate Edging Stainless Steel Sink

Huntington Brass Faucet 1 USB Receptacle

Appliances

30" Gas Range Power Range Hood with Light 18 Cu.Ft. No-Frost Refrigerator

<u>Baths</u>

60" Tub/Shower Tub Overflows Shower Drain with Removable Strainer 1.6 Gallon Per Flush Toilets Laminate Countertops with Laminate Edging Lighted Vent Fan in Each Bath Brushed Nickel Strip Light in Master Bath Brushed Nickel Cabinet Hardware Base Shelf in Vanities 36" High Master Bath Vanity 33" High Secondary Bath Vanities Anti-Scald Faucets in Tub/Shower China Sinks with Overflows & Pop-Up Drains Huntington Brass Faucets

<u>Bedrooms</u>

Switched Receptacles Egress Window in Each Bedroom Wire Shelving in Wardrobes

Utilities

Plumb for Washer Wire and Vent for Electric Dryer 200 AMP Electrical Service Copper Wiring Throughout Water Shut-Off Valves Where Accessible Water & Drain Lines Stubbed Through Floor

Insulation

R-19 Fiberglass Insulation in Walls R-31 Avg. Blown Insulation in Ceiling

Exterior

White Coach Light at Front Door Vinyl Exterior Siding with OSB Sheathing

Two GFI-Protected Exterior Receptacle 25 Year Shingle Roof with Vented Soffits & Ridge Vent

3/0x6/8 6-Panel Steel Front & Rear Door with Deadbolt Lock Low-E, Argon Filled Vinyl Insulated

Windows 12" Louvered Shutters on Front

Door Side

Construction

2x10 Transverse Floor System on 16" Centers**
2x6 Exterior Walls on 16" Centers**
5/12 Roof Pitch, 10" Eaves, Flush Overhangs
40# Roof Load
90 Mile Exposure C Wind Load Design Wind Wrap Air Infiltration Barrier

**NOTE: Spacing for Framing Members may vary due to Design Requirements

Bold Items are Factory Select

